Ĵ

AKRON DISPERSIONS, INC.

MATERIAL SAFETY DATA SHEET

Page 1 of 3

SECTION 1 PRODUCT IDENTIFICATION & EMERGENCY INFORMATION

PRODUCT NAME: **Bostex 422** CHEMICAL NAME: Aqueous Mixture of Zinc Oxide(CAS# 1314-13-2), Sodium Salts of Polymerized AlkyInaphthalenesulfonic Acid(CAS# 9084-06-4/36290-04-7) MANUFACTURER: Akron Dispersions, Inc. 3291 Sawmill Road P.O. Box 4195 Akron, Ohio 44321 TELEPHONE NUMBER: (330)666-0045 EMERGENCY TELEPHONE NUMBER: (330)666-0045 FAX: (330)666-7842

SECTION 2 HAZARDOUS INGREDIENT INFORMATION

Zinc Oxide(CAS# 1314-13-2): 59.94% Lead(CAS# 7439-92-1): 0.0006% Cadmium(CAS# 7440-43-9): 0.003% Formaldehyde(CAS# 50-00-0): <0.0017% Naphthalene(CAS# 91-20-3): <0.00065% Quinoline(CAS# 91-22-5): <0.0065%

SECTION 3 HAZARDS IDENTIFICATION

Health Hazards(Acute and Chronic): May cause irritation to eyes and skin of sensitive individuals. May contain <0.0017% Formaldehyde, <0.00065% Naphthalene, and <0.0065% Quinoline, known to the State of California to cause cancer.
 HMIS: Health 0. Elammability 0. Personal Protection B.

HMIS: Health-0 Flammability-0 Reactivity-0 Personal Protection-B

SECTION 4 FIRST AID MEASURES

Eye Contact: Flush with large amounts of water for at least 15 minutes. Consult a physician if irritation persists.

Skin Contact: Wash affected area with soap and water. Consult a physician if irritation persists. Inhalation: Remove to fresh air. If breathing is difficult, seek medical attention. Ingestion: Seek medical advice.

SECTION 5 FIRE & EXPLOSION HAZARD

Flashpoint: N/D Flammable Limits: N/D General Hazard: Wear MSHA-NIOSH approved Self-Contained Breathing Apparatus Extinguishing Media: CO₂, Dry Chemical, Waterspray, Foam Decomposition Products Under Fire Conditions: Oxides of Carbon, Sulfur, and Sodium

SECTION 6 ACCIDENTAL RELEASE MEASURES

Steps To Be Taken In Case Material Is Released Or Spilled: Absorb with inert material. Sweep, vacuum, or shovel into appropriate container.

SECTION 7 HANDLING AND STORAGE

Storage: Store in a cool, dry area. Storage Temperature: Above 32°F

SECTION 8 EXPOSURE CONTROLS AND PERSONAL PROTECTION

OSHA Regulation 29CFR1910.1000 requires the following PEL Limits: N/D The ACGIH recommends the following Occupational Exposure Limit: N/D Personal Protection: Gloves and Goggles recommended Ventilation: Local Exhaust

SECTION 9 TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Product Appearance: White to Off-White Liquid

Boiling Point(°F): 212 Vapor Pressure(@150°C): N/A Vapor Density: N/A Solubility in Water: Miscible pH: 9.0-11.0 Freezing Point(°F): 32 Specific Gravity(Approx.): N/D % Volatile by Volume: 40% Evaporation Rate: N/A

SECTION 10 STABILITY AND REACTIVITY DATA

Stability: Stable
Conditions To Avoid Instability: None Known
Materials And Conditions To Avoid Incompatibility: Magnesium, Strong Acids, Strong Bases. Zinc Oxide has been reported to cause a violent explosion when mixed in a chlorinated rubber batch. Hazardous
Decomposition Products: Oxides of Carbon, Sulfur, and Sodium
Hazardous Polymerization: Will Not Occur
Conditions To Avoid Hazardous Polymerization: None Known

SECTION 11 TOXICOLOGICAL INFORMATION

Carcinogenicity(NTP/IARC/OSHA): None. May contain <0.0017% Formaldehyde, <0.00065% Naphthalene, and <0.0065% Quinoline, known to the State of California to cause cancer.

SECTION 12 ECOLOGICAL INFORMATION

Not determined

SECTION 13 DISPOSAL

Waste Disposal Method: Dispose per Local, State, and Federal Regulations

SECTION 14 TRANSPORT INFORMATION

DOT: Not a DOT controlled material(United States).

SECTION 15 REGULATORY INFORMATION

TSCA: All ingredients of this product appear on the TSCA Inventory

SARA Title III-Section 313: This product contains Zinc Compounds, Lead, and Cadmium, listed chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and of 40 CFR 372.

SECTION 16 OTHER INFORMATION

Prepared By: D. Hunsicker Date: January 7, 2010

The information in this MSDS was compiled from sources which we believe are accurate and reliable. However, this information is provided without any warranty, expressed or implied, regarding its correctness. It is the user's responsibility to determine the suitability of any material for a specific purpose and adopt such safety precautions as may be necessary. We do not assume responsibility and expressly disclaim liability for loss, damage, or expense arising out of, or in any way connected with the handling, storage, use, or disposal of this product.